

Amendments to the Specification:

Please replace the specification with the attached substitute specification (a marked up copy of the copy is also attached). No new matter has been added.

Please replace the abstract with the following amended abstract:

A user interface of a machine tool ~~comprises~~includes a display (1) which ~~that~~ is divided into at least ~~two regions~~ (2, 4) ~~a~~ first display region and a second display region. ~~The first display region permanently displays~~ a main menu (3) which ~~is permanently displayed in the first display region~~ (2), ~~in particular, and the main menu includes~~ a menu bar, ~~for selecting that provides a selection of~~ different main modes (31-37) of the user interface. ~~Each main mode is associated with a main window~~ (51-57) ~~which~~that is opened in the second display region (4) ~~in accordance with~~when a main mode is selected in the main menu (3), ~~wherein, at~~ At least one of the main windows (51-57) ~~comprises~~includes a permanently displayed submenu ~~for selecting that provides selection of~~ different submodes, (61-64) ~~and with each submode being associated with a subwindow~~ ~~which~~that is opened ~~in accordance with the selected~~ ~~when an associated submode is selected~~, ~~and~~ One or more of the main windows and the subwindows include input fields. ~~with a~~ The user interface also includes an input unit for selecting the individual modes (31-37; 61-67) and for processing the input fields (14) provided in a window, (51-57), ~~wherein the~~ The display (1) permanently displays which one of the main modes is selected.